

Updated S  
08/798,703

(FILE 'HOME' ENTERED AT 10:43:08 ON 22 MAR 2001)

FILE 'USPATFULL' ENTERED AT 10:43:46 ON 22 MAR 2001

L1 14 SEA ADVERTIS? PUBLISHER#  
L2 287 SEA ADVERTIS? (P) AVAILABILIT?  
L3 321 SEA ADVERTIS? (P) CAPACIT?  
L4 21 SEA L2 AND L3  
L5 10 SEA L4 (P) HOST?  
L6 1 SEA US5568612/PN  
L7 0 SEA L6 AND L5  
L8 0 SEA TCP/IP  
L9 4254 SEA "TCP/IP"  
L10 1 SEA L5 AND L9  
D  
D FRO  
D KWIC  
L11 2 SEA (US5732219 OR US5696901)/PN  
L12 18543 SEA ADVERTIS?  
L13 1 SEA L12 AND L11  
D KWIC  
L14 82360 SEA AVAILABILITY  
L15 360043 SEA CAPACITY  
L16 0 SEA L11 AND L14  
L17 0 SEA L11 AND L15  
L18 1 SEA L6 AND L12  
L19 0 SEA L18 AND L14  
L20 1 SEA L18 AND L15  
D KWIC  
L21 147 SEA CLIENT# (P) REMOTE? CONTROL?  
L22 0 SEA L6 AND L21  
L23 1 SEA L6 AND REMOT?  
D KWIC  
L24 1 SEA HOST? AND L6  
D KWIC  
L25 1 SEA L6 AND L9  
D KWIC

FILE HOME

FILE USPATFULL

FILE COVERS 1971 TO PATENT PUBLICATION DATE: 20 Mar 2001 (20010320/PD)

FILE LAST UPDATED: 20 Mar 2001 (20010320/ED)

HIGHEST PATENT NUMBER: US8345926

CA INDEXING IS CURRENT THROUGH 20 Mar 2001 (20010320/UPCA)

ISSUE CLASS FIELDS (/INCL) CURRENT THROUGH: 20 Mar 2001 (20010320/PD)

REVISED CLASS FIELDS (/NCL) LAST RELOADED: Dec 2000

USPTO MANUAL OF CLASSIFICATIONS THESAURUS ISSUE DATE: Oct 2000

>>> Page images are available for patents from 1/1/1997. Current <<<  
>>> week patent text is typically loaded by Thursday morning and <<<  
>>> page images are available for display by the end of the day. <<<  
>>> Image data for the /FA field are available the following week. <<<

>>> Complete CA file indexing for chemical patents (or equivalents) <<<  
>>> is included in file records. A thesaurus is available for the <<<  
>>> USPTO Manual of Classifications in the /NCL, /INCL, and /RPCL <<<  
>>> fields. This thesaurus includes catchword terms from the <<<

>>> USPTO/MOC subject headings and subheadings. Thesauri are also <<<  
>>> available for WIPO International Patent Classification <<<  
>>> (IPC) Manuals, editions 1-6, in the /IC1, /IC2, /IC3, /IC4, <<<  
>>> /IC5, and /IC (/IC6) fields, respectively. The thesauri in <<<  
>>> the /IC5 and /IC fields include the corresponding catchword <<<  
>>> terms from the IPC subject headings and subheadings. <<<

This file contains CAS Registry Numbers for easy and accurate  
substance identification.

Media-Dependent  
Receive Statistic

Description

CRC Total number of Cyclic Redundancy Check errors detected by the LBP-Remote

Missed Frames Number of packets missed due to lack of space in the receive buffer, or the controller is in the. . .

DETD . . . upon any device external to the printer. Furthermore, the initial default configuration may be loaded and subsequently modified from a **remote** location over the LAN through the NEB's serial or parallel interfaces.

DETD 4n. Downloading Executable Files Into The NEB From A Remote LAN Location

DETD . . . updated executable files across the LAN from the network administrator's PC 14 to the NEB 2. Furthermore, network administrator can **remotely** alter the executable files stored in DRAM 220 of NEB 2, as desired.

DETD Thus, the network administrator can alter the operation of NEB 2 by **remotely** sending new operational files to be stored and to be executed from DRAM 220.

DETD . . . and address bus 251 is DRAM 220. DRAM 220 is capable of storing a ROM firmware image downloaded from a **remote** LAN device into one portion of its memory area (see section 4o above), and application process steps into another portion. . .

DETD 4q. **Remotely** Altering Firmware

DETD The method for **remotely** altering firmware in EPROM 222 will be discussed in more detail below and with reference to the flowchart illustrated in. . .

DETD . . . However, the NEB can be reconfigured subsequently by the customer. That is, a network administrator may download data from a **remote** LAN device, which data may contain anything from a patch code, to manufacturing test routines, to entire firmware updates to. . .

DETD . . . by sending executable files across the LAN from the network administrator's PC 14 to NEB 2. The network administrator can **remotely** alter the ROM firmware image in EPROM 222, as desired.

DETD . . . still be stored in a non-volatile way. (Of course, as discussed in paragraph 4q, the MAC address could also be **remotely** flashed into the EPROM at the same time the RAM firmware image is updated, after NEB 2 is coupled to. . .

=> s host? and l6

107742 HOST?  
L24 1 HOST? AND L6

=> d kwic

L24 ANSWER 1 OF 1 USPATFULL  
PI US 5568612 19961022

<--

SUMM . . . merely accepting information from the LAN and printing such information on a hard copy. Moreover, such printers usually required a host personal computer ("PC") to effectively manage the flow of data to the printer, i.e., to act as a "server" for the printer. This almost always required that the host PC be dedicated solely to the printer server task.

SUMM . . . those servers are available. This is because the Novell-compatible Server Advertising Protocol ("SAP") assumes that each network node is the host to only a single network server. Accordingly, even if more than one server were provided in a single network node, . . .

=> s 16 and 19

L25 1 L6 AND L9

=> d kwic

L25 ANSWER 1 OF 1 USPATFULL

PI US 5568612 19961022

<--

DETD . . . Ethernet data received over the LAN may be one of the following

software protocols: e.g. NetWare.RTM. over SPX/IPX; UNIX over TCP/IP; or Mac Systems 7 over AppleTalk. Basically, the software protocol type may be determined according to the frame packet type. . .

DETD . . . over a LAN bus using SPX/IPX operating protocol, while a UNIX-compatible operating system communicates over the LAN bus using a TCP/IP operating protocol. Other operating systems, such as the AppleTalk.RTM. operating system provided by Apple Corporation, use respectively different operating protocols. . .

DETD UNIX-compatible operating protocols are illustrated at reference numerals 335, 336 and 337. More specifically, 335 and 336 comprise a TCP/IP operating protocol stack (or tower) by which UNIX-compatible application programs communicate to LAN bus 6 via LSL. UNIX-compatible network application. . .

DETD . . . UNIX operating system to use the same frame packet type; it is the operating system protocols (SPX/IPX for Novell and TCP/IP for UNIX) which determine which one of the operating systems in a multiprotocol environment is currently communicating on the LAN.

DETD . . . which has the proper IPX header. Then, PRESCAN binds simultaneously through LSL through all three frame packet types having a

TCP/IP protocol tower. PRESCAN determines the frame packet type being used by the UNIX-compatible operating system in accordance with the data group having the proper TCP/IP header.

DETD . . . LSL to bind simultaneously to a plurality of frame packet types

corresponding to the second operating system protocol, such as TCP/IP for a UNIX operating system. The network driver monitors the LAN communication bus to capture broadcast traffic for the second. . . the packet types. The PRESCAN module prescans each data group for the presence of a predetermined header, such as the TCP/IP header for UNIX, and stores the frame packet type corresponding to the data group having the predetermined header.

L7 ANSWER 1 OF 1 USPATFULL

PI US 5568612 19961022

<--

DETD . . . Ethernet data received over the LAN may be one of the following

software protocols: e.g. NetWare.RTM. over SPX/IPX; UNIX over TCP/IP; or Mac Systems 7 over AppleTalk. Basically, the software protocol type may be determined according to the frame packet type. . .

DETD . . . over a LAN bus using SPX/IPX operating protocol, while a UNIX-compatible operating system communicates over the LAN bus using a TCP/IP operating protocol. Other operating systems,

such as the AppleTalk.RTM. operating system provided by Apple Corporation, use respectively different operating protocols. . .

DETD UNIX-compatible operating protocols are illustrated at reference numerals 335, 336 and 337. More specifically, 335 and 336 comprise a TCP/IP operating protocol stack (or tower) by which UNIX-compatible application programs communicate to LAN bus 6 via LSL. UNIX-compatible network application. . .

DETD . . . UNIX operating system to use the same frame packet type; it is the operating system protocols (SPX/IPX for Novell and TCP/IP for UNIX) which determine which one of the operating systems in a multiprotocol environment is currently communicating on the LAN.

DETD . . . which has the proper IPX header. Then, PRESCAN binds simultaneously through LSL through all three frame packet types having

a

TCP/IP protocol tower. PRESCAN determines the frame packet type being used by the UNIX-compatible operating system in accordance with the data group having the proper TCP/IP header.

DETD . . . LSL to bind simultaneously to a plurality of frame packet types

corresponding to the second operating system protocol, such as TCP/IP for a UNIX operating system. The network driver monitors the LAN communication bus to capture broadcast traffic for the second. . . the packet types. The PRESCAN module prescans each data group for the presence of a predetermined header, such as the TCP/IP header for UNIX, and stores the frame packet type corresponding to the data group having the predetermined header.

L11 ANSWER 1 OF 1 USPATFULL

PI US 5568612 19961022

<--

DETD

. . . Printer

NEB-to-Network

CPSOCKET (30KB)

Concurrent multi-  
protocol operation

communication in

NEB EPROM

NEB Environment in (15KB)

Monitor, loader,  
POST, etc.

NEB EPROM

Extensions to

CPCONSOL.EXE

(180KB)

Remote Control &  
Stats, Auto-

NetWare .RTM.

PCONSOLE for Printer

CPINIT.EXE

(120KB)

Reconfiguration,  
Print Job

Control/Configuration

in Administrator's

Logs/Statistics

PC 14

---

DETD In summary, at Step S28, a method for **remotely controlling** a manually-operable function of a networked printer through an interactive network board having a LAN interface for LAN communication, comprises. . .

and downloading of new applets. To ensure widespread **availability** of the new features made possible by the present architecture, the customer premise equipment may be provided to end users. . . . being amortized over the services sold to the user through the equipment. Additionally, the service provider may collect fees from **advertisers** to subsidize the cost of the equipment.

DETD . . . . as an IP proxy server such that each of the devices connected to the server utilizes transmission control protocol/Internet protocol (TCP/IP) protocol. This configuration allows any device associated with the ISD to access the Internet via an IP connection through the. . . the ISD 22 is configured as an IP proxy server, it may accommodate additional devices that do not support the TCP/IP protocol. In this embodiment, the ISD 22 may have a proprietary or conventional interface connecting the ISD 22 to any. . .

DETD . . . . two or more twisted pair connected with the local office. The videophone can contain Win32 application programable interfaces (APIs) supporting TCP/IP, POP3, RAS, and TAPI protocols with a built in browser. One of the twisted pair will access the AT&T server. . . .

DETD A requirement of the touch screen services is **availability** of a data link to the server. In later phases of implementation, a DSL link to the home is provided. . . . built-in motion detector is triggered by someone nearby. During these periods of local presence, the AT&T server will put up **advertising** and personal information on the screen and be available to support touch activated services (e.g., calling, CLASS services), and directory. . . .

DETD . . . . (LAN) Intranet access (FIGS. 13 and 14). For business customers, the architecture supports secure electronic commerce and personalized delivery of **advertising** to consumers with the **capacity** to tailor the **advertising** campaign to the consumer's profile (FIG. 17).

CLM What is claimed is:

13. A network server platform of a telecommunications network for **hosting** a plurality of services, said network server platform comprising a memory for storing a user profile, said user profile containing. . . .

14. A network server platform of a telecommunications network for **hosting** a plurality of services, said network server platform comprising a memory for storing a user profile, said user profile containing. . . .

cls 26-27

L4 ANSWER 1 OF 1 USPATFULL

PI US 5568612 19961022

<--

DETD . . . CRPRINTER. If CPSEVER is selected, it is necessary to  
designate the name of the print server assigned to the NEB,  
**password**, application buffer size, queue service mode, form  
numbers, the printer number of the printer in which the NEB resides,  
the. . .

L10 ANSWER 1 OF 1 USPATFULL  
United States Patent

Patent Number: 6044403  
Date of Patent: 28 Mar 2000

-----  
Network server platform for internet, JAVA server and video application server

Inventor(s): Gerszberg, Irwin, Kendall Park, NJ, United States  
Huang, Kenny Xiaojian, Somerset, NJ, United States  
Kwabi, Christopher K., Englewood, NJ, United States  
Martin, Jeffrey S., Dover, NJ, United States  
Miller, II, Robert Raymond, Township of Morris, Morris County,  
NJ, United States  
Russell, Jesse Eugene, Piscataway, NJ, United States  
Assignee: AT&T Corp, New York, NY, United States (U.S. corporation)  
Appl. No.: 97-1354  
Filed: 31 Dec 1997

Int. Cl. .... G06F013-00  
Issue U.S. Cl. .... 709/225.000; 709/217.000; 709/223.000; 709/238.000  
Current U.S. Cl. .... 709/225.000; 709/217.000; 709/223.000; 709/238.000  
Field of Search ..... 709/201; 709/202; 709/203; 709/217; 709/219; 709/223;  
709/224; 709/225; 709/227; 709/229; 709/238; 709/300;  
709/250

Reference Cited

PATENT DOCUMENTS

Patent Number	Date	Class	Inventor
US 4456925	Jun 1984		Skerlos et al.
US 4620289	Oct 1986		Chauvel
US 4725694	Feb 1988		Auer et al.
US 4916441	Apr 1990		Gombrich
US 5014267	May 1991		Tompkins et al.
US 5157717	Oct 1992		Hitchcock
US 5335276	Aug 1994		Thompson et al.
US 5393964	Feb 1995		Hamilton et al.
US 5406615	Apr 1995		Miller, II et al.
US 5488412	Jan 1996		Majeti et al.
US 5512935	Apr 1996		Majeti et al.
US 5534913	Jul 1996		Majeti et al.
US 5546316	Aug 1996		Buckley et al.
US 5561604	Oct 1996		Buckley et al.
US 5572005	Nov 1996		Hamilton et al.
US 5583965	Dec 1996		Douma et al.
US 5584054	Dec 1996		Tyneski et al.
US 5587735	Dec 1996		Ishida et al.
US 5610910	Mar 1997	370/351.000	Focsaneanu et al.
US 5619684	Apr 1997		Goodwin et al.
US 5644628	Jul 1997		Schwarzer et al.
US 5671267	Sep 1997		August et al.
US 5682195	Oct 1997		Hendricks et al.
US 5684918	Nov 1997		Abecassis
US 5740231	Apr 1998	379/088.220	Cohn et al.
US 5761662	Jun 1998	707/010.000	Dasan
US 5796952	Aug 1998	709/224.000	Davis et al.

US 5850433	Dec 1998	379/201.000	Rondeau
US 5867495	Feb 1999	370/352.000	Elliott et al.
US 5878130	Mar 1999	379/265.000	Andrews et al.
US 5889958	Mar 1999	709/229.000	Willens
US 5892909	Apr 1999	709/201.000	Grasso et al.
US 5893091	Apr 1999	707/003.000	Hunt et al.

#### OTHER PUBLICATIONS

US Patent Application 08/943,312 filed Oct. 14, 1997, entitled Wideband Communication System for the Home; to Robert R. Miller, II and Jesse E. Russell, 21 pages.

US Patent Application 08/858,170 filed May 14, 1997, entitled Wide Band Transmission Through Wire, to Robert R. Miller, II, Jesse E. Russell and Richard R. Shively, 15 pages.

Art Unit - 278

Primary Examiner - Vu, Viet D.

-----

14 Claim(s), 21 Drawing Figure(s), 21 Drawing Page(s)

#### ABSTRACT

A new architecture capable of utilizing the existing twisted pair interface between the customer services equipment and the local office is used to provide a vast array of new services to customers. Using an intelligent services director (ISD) at the customer services equipment and a facilities management platform (FMP) at the local office, new services such as simultaneous, multiple calls (voice analog or digital), facsimile, Internet traffic and other data can be transmitted over the existing single twisted pair using xDSL transmission schemes. New services such as the implementation of Internet connectivity, videophone, utility metering, broadcasting, multicasting, bill viewing, information pushing in response to a user profile, directory look-up and other services can be implemented via a network server platform via this architecture. A network server platform for **hosting** a plurality of services comprises, for example, a memory for storing a user profile, the user profile containing interests of a user, and for storing information related to their interests and a controller for controlling the collection of information from information servers and for pushing the collected information to the user in accordance with their defined priority.

=> d kwic

L10 ANSWER 1 OF 1 USPATFULL

AB . . . look-up and other services can be implemented via a network server platform via this architecture. A network server platform for **hosting** a plurality of services comprises, for example, a memory for storing a user profile, the user profile containing interests of.

SUMM . . . connected device and dedicated applications for specific devices such as bill viewing from a video phone. The network server platform **hosts** the plurality of services and comprises, for example, a memory for storing a user profile, the user profile containing interests. . .

DETD . . . to the FMP 32 and thereafter to the NSP 36 for reinitialization

L11 ANSWER 1 OF 1 USPATFULL

PI US 5568612 19961022

<--

DETD

. . . . Printer

NEB-to-Network

CPSOCKET (30KB)

Concurrent multi-  
protocol operation

communication in

NEB EPROM

NEB Environment in (15KB)

Monitor, loader,  
POST, etc.

NEB EPROM

Extensions to

CPCONSOL.EXE

(180KB)

Remote Control &  
Stats, Auto-

NetWare .RTM.

PCONSOLE for Printer

CPINIT.EXE

(120KB)

Reconfiguration,  
Print Job

Control/Configuration

in Administrator's

Logs/Statistics

PC 14

---

DETD In summary, at Step S28, a method for **remotely controlling** a manually-operable function of a networked printer through an interactive network board having a LAN interface for LAN communication, comprises. . .

L3 ANSWER 2 OF 2 USPATFULL

PI US 5568612 19961022

<--

DETD . . . are provided between a plurality of LANs, as shown in FIG. 2,  
such that resources, including printers, can be shared "**internet**  
" i.e., from one LAN to another.